2. Only those positions are combined which have different characters to the left. Thus it guarantees left-maximality of the repeats. Recall that we consider processing the edge v → w and let a be the first character of the label of this edge. The annotation already computed for x was inherited along edges outgoing from v, that are different from v → w. Thus the first character of the label of such an edge, say σ, is different from a. Now since ν is the repeated substring, σ and a are characters to the right of ν. As a consequence, only those positions are combined which have different characters to the right. In other words, the algorithm also guarantees right-maximality of the repeats.

As soon as for the current edge the repeats are reported, the algorithm computes the union  $A(v,\sigma) \cup A(w,\sigma)$  for all characters  $\sigma$ , i.e. the annotation is inherited from node w to node v. In this way, after processing all edges outgoing from v, this node is annotated by the set of positions where  $\nu$  occurs, and this set is divided into (possibly empty) disjoint subsets  $A(v,\sigma_1),\ldots,A(v,\sigma_r)$ , where  $\Sigma = {\sigma_1,\ldots,\sigma_r}$ .

**Example 9.17** The suffix tree of the string s = xggcgcygcgccz is shown in Figure 9.8. We assume the leaf annotation of it (as shown in Figure 9.9) is already determined.

Proceeding from leaves 8 and 3, the bottom up traversal of the suffix tree for xggcgcygcgcz begins with node v whose path-label is gcgc of depth q=4. This node has two children which do not have the same character to their left (y vs. g). The node is annotated with (g,3) and (y,8). Because our repeat is also left-maximal, it is reported: ((3,3+4-1),(8,8+4-1))=((3,6),(8,11)), as can be seen in Figure 9.10, which shows the annotation for a large part of the suffix tree and some repeats.




Figure 9.10: The annotation for a large part of the suffix tree of Figure 9.9 and some repeats.

Next comes the node v with path-label gc of depth two. The algorithm starts by processing the first edge outgoing from v. Since initially there is no annotation for v, no repeat is reported and v is annotated with the label of leaf 10: (c,10). Then the second edge is processed. This means that the annotation (g,3), (y,8) for w with path-label gcgc is combined with the annotation (c,10). The new annotation for v becomes (c,10), (y,8), (g,3). This gives the repeats ((8,9),(10,11)) and ((3,4),(10,11)). Finally, the third edge is processed. (c,10) and (c,5) cannot be combined, see condition 2 above. So only the repeats ((5,6),(8,9)) and ((3,4),(5,6)) are reported, resulting from the combination of (y,8) and (g,3) with (c,5). The final annotation for v is (c,10), (y,8), (g,3), (c,5), which can also be read as  $A(v,g) = \{3\}$ ,  $A(v,c) = \{5,10\}$  and  $A(v,y) = \{8\}$ . We leave further processing up to the reader.